

# ADP-602K-IROA



## Features

- 1/3" Sony Super HAD CCD
- Chinese and English OSD menu setting, use wire control
- Wide dynamic effects with digital, electronic shutter adjustable
- 3D digital noise reduction, Digital Zoom: X1.0 ~ X3.0
- With light suppression; Wide Supply 10V ~ 16V
- 8mm lens / 2 high-power lamps, effective distance of 60m for residential entrances, car parks and other places according to license plate

## Specification

Model / Specification	ADP-602K-IROA
<b>Electronic</b>	
Input Voltage	12V DC±10%
Power Consumption	4.0W
<b>Video</b>	
Image Sensor	1/3" Sony Super HAD II CCD
Effective Pixels	PAL: 795(H) x 596(V) NTSC: 811(H) x 508(V)
Signal System	PAL/NTSC
Resolution	600TVL
Minimum Illumination	0Lux (IR ON)
S/N Ratio	50dB above (AGC)
Gamma Ratio	0.45
Video Output	1.0Vp-p / 75 Ω
<b>OSD Main Setting</b>	
Menu	OSD menu control
Synchronization System	Internal
D&N Mode	NO / OFF(adjustable)
Electronic Shutter Speed	1/50(1/60) - 1/100000 sec
Auto Gain Control	Medium / Low / High / Off
White Balance	AWC/ATW/Manual/Lock Selection
Back Light Compensation	ON / OFF(adjustable)
Digital Noise Reduction	3D digital noise reduction (in / Low / High / Off)
Motion Detection	ON / OFF(adjustable)
Privacy Masking	Set up to 4
Languages	Chinese / English menu
<b>Lens</b>	
Lens	8mm lens
Lens Type	M12 Mount
<b>Environment</b>	
Working Temperature/Humidity	-10°C~ 55°C / 30% ~ 95% RH
Storage Temperature/Humidity	-20°C ~ 70°C / 30% ~ 80% RH
<b>Mechanical</b>	
Sizes	100(W)×96(H)×184(L)mm
Weight	1.5kg
IR LED	2pcs High Power Light
Effective Range	60m
Protection Class	IP65

Design and specification are subject to change without prior notice

