

ADP70FR

AHD Mini 10x IR Outdoor

Features

- 1.3 Megapixel, 10X optical zoom F1.6~F2.8
- OSD menu available / IR distance 50M
- IR illumination & power consumption is variable dependant on zoom factor
- Keep original analog system
- AHD lossless video real time transmission
- Long distance transmission up to 500 meters
- 4.5" Total Metal body construction, IP66 rate protection



Specification

Model / Specification	ADP70FR
Image Sensor	1/3" CMOS SONY238
Effective pixels	960P (1280*960)
Total pixels	1.3 Megapixel
Lens	10x optical zoom
3D NR	Support
Iris	F1.6~F2.8
Min. illumination	Color: 0.5Lux \ B/W: 0.05Lux
BLC	Support
BW	Indoor/Outdoor/Auto/Manual
D/N	IR-CUT
S/N Ratio	≥50dB
Pan range	360°continuous rotation
Tilt range	0°~93° auto flip 180°
Manual Pan speed	0.02~200°/S
Manual Tilt speed	0.02~80°/S
Preset Points	220
Privacy zone	Support
Guard Tours	3 groups
Guard Points	Max.16 points, dwell time user selectable
Operating temperature	Indoor:0°C~+40°C Outdoor: -40°C~+60°C
Operation menu	English
Pan and Tilt position display	Support
Humidity	≤95% Non Condensing
Power	DC12V 3A
Consumption	< 15W
Lightning Protection	Transient voltage 6000V
Video interface output	AHD
Communication mode	RS485
Related validation	IP66,CE,FCC,RoHs
Auto Control IR LED	PWM
LEDs	Array 42Mil
IR distance	Up to 50 meters
Support ambient light detection	IR illumination on 1-15 grades selectable

Design and specifications are subject to change without prior notice

