

ADV15A2P-IR



Key Features

- Compact design
- DIS
- IR cut filter with auto switch
- Min. illumination: 0.1 Lux @ F1.2 (0 Lux with IR)
- Auto white balance, auto gain control, electronic shutter control and backlight compensation
- Smart IR mode
- Internal Synchronization
- Advanced Engineering Design, High Reliability
- 3-axis (pan/tilt/rotation) positioning allows adjustment for optimum Surveillance angles and position
- Adopt a mount for routing cables through
- Ingress Protection: IP66

Specification

Model	ADV15A2P-IR
Parameter	700TVL DIS IR Bullet Camera (ICR & Weather-proof)
Camera	
Image Sensor	1/3" DIS
Signal System	PAL/NTSC
Effective Pixels	976 (H) × 496 (V)
Min. Illumination	0.1 Lux @ (F1.2,AGC ON),0 Lux with IR
Shutter speed	PAL: 1/50 s to 1/100,000 s NTSC: 1/60 s to 1/100,000 s
Lens	3.6 mm (2.8mm,6mm optional)
	Angle of view: 68.4° (3.6 mm)
Lens Mount	M12
Angle Adjustment	Pan: 0 - 360°, Tilt: 0 - 90°, Rotation: 0 - 360°

Day & Night	IR cut filter with auto switch
Horizontal Resolution	700 TVL
Synchronization	Internal synchronization
Video Output	1Vp-p composite output (75 Ω/BNC)
S/N Ratio	More than 62 dB
General	
Working Temperature/Humidity	-40 °C - 60 °C (-40 °F - 140 °F) Humidity 90% or less (non-condensing)
Power Supply	12 V DC ± 10%
Power Consumption	Max. 1.8 W (Max. 4 W with IR cut filter on)
Ingress Protection	IP66
IR Range	Approx. 10 to 20 meters
Dimensions	Φ70×149.5 mm (Φ2.76" ×5.89")
Weight	360 g (0.79 lbs)

Dimensions

